



25 Editors - Outliner

Table of content

Detailed table of content.....	2
Outliner.....	7
General hotkey functionality.....	7
Extended Functionality.....	8
Collections.....	8
Header - All Modes.....	8
Switch to Properties Editor / Outliner.....	8
Display Mode.....	8
View Menu.....	9
Search Field.....	10
Right Click Menus.....	11
Outliner Scene Operation.....	11
Outliner Data Operation.....	11
Collection.....	12
Object Menu.....	18
Outliner ID Data Operation.....	20
Outliner Animation Data Property.....	21
Outliner Modifier Operation.....	21
Level Restrictions.....	22
Scenes Mode.....	23
Collection Menu.....	23
Remove From Collection.....	24
Remove From all Unlinked Collections.....	24
Add selected To Active Collection.....	24
Remove Selected From Active Collection.....	24
Add Collection.....	24
New Scene.....	24
Filter.....	25
View Layer Mode.....	26
Collection Menu.....	26
Remove From Collection.....	26
Remove From all Unlinked Collections.....	27
Add selected To Active Collection.....	27
Remove Selected From Active Collection.....	27
Add Collection.....	27
Filter.....	27
Sequence Mode.....	29
Sync Outliner Selection.....	29
Blender File Mode.....	29
Filter.....	29
Outliner Library Operation.....	29
Data API Mode.....	30
Header tools.....	30
Library Override Mode.....	31
Library Override View Mode.....	31
Filter options.....	31
Filter.....	32

Unused Data Mode.....	32
Clean Up.....	32
Filter.....	33
Status column.....	33
Hotkey only functionality.....	34
Insert Keyframe - I.....	34
Delete Keying Set Keyframe - Alt I.....	34
Hide - H.....	34
Unhide - Alt H.....	34

Detailed table of content

Detailed table of content

Detailed table of content.....	2
Outliner.....	7
General hotkey functionality.....	7
Extended Functionality.....	8
Collections.....	8
Header - All Modes.....	8
Switch to Properties Editor / Outliner.....	8
Display Mode.....	8
View Menu.....	9
Show Active.....	9
Show One Level.....	9
Hide One Level.....	9
Expand / Collapse All.....	9
Show Hierarchy.....	9
Box Select.....	9
Select All.....	9
Deselect All.....	9
Invert Selection.....	9
Manage Unused Data.....	10
Pie menus.....	10
Area.....	10
Horizontal Split.....	10
Vertical Split.....	10
Duplicate Area into new Window.....	10
Toggle Maximize Area.....	10
Toggle Fullscreen Area.....	10
Close Area.....	10
Search Field.....	10
Right Click Menus.....	11
Outliner Scene Operation.....	11
Delete.....	11
Copy Settings.....	11
Linked Copy.....	11
Full Copy.....	11
Mark as Asset, Clear Asset, Clear Asset (Set Fake User).....	11
Outliner Data Operation.....	11
Select.....	11

Deselect.....	11
Hide.....	12
Unhide.....	12
Select Linked.....	12
Mark as Asset, Clear Asset, Clear Asset (Set Fake User).....	12
Collection.....	12
New Nested.....	12
New.....	12
Duplicate Collection.....	12
Duplicate Linked.....	12
Copy.....	12
Paste.....	12
Delete.....	13
Delete Hierarchy.....	13
Select Objects.....	13
Deselect Objects.....	13
Instance to Scene.....	13
Unlink.....	13
Visibility.....	13
Isolate.....	13
Show All Inside.....	13
Hide.....	13
Set Color Tag.....	13
ID Data.....	14
Unlink.....	14
Make Local.....	14
Add Library Override.....	14
Make Single User.....	14
Delete.....	14
Remap Users.....	14
Copy.....	15
Paste.....	15
Make Library Override Editable.....	15
Make Library Override Hierarchy.....	15
Reset Library Override.....	15
Reset Library Override Hierarchy.....	15
Resync Library Override Hierarchy.....	15
Resync Library Override Hierarchy Enforce.....	15
Delete Library Override Hierarchy.....	15
Clear Single Library Override.....	15
Copy.....	15
Paste.....	16
Add Fake User.....	16
Clear Fake User.....	16
Rename.....	16
Select Linked.....	16
Make Library Override.....	16
Selected.....	16
Content.....	16
Selected & Content.....	16
Reset Library Override.....	16
Selected.....	17
Content.....	17

Selected & Content.....	17
Clear Library Override.....	17
Selected.....	17
Content.....	17
Selected & Content.....	17
Troubleshoot Library Override.....	17
Resync.....	17
Resync Enforce.....	17
Delete.....	17
Mark as Asset.....	17
Clear Asset.....	18
Clear Asset (Set Fake User).....	18
Object Menu.....	18
Select.....	18
Select Hierarchy.....	18
Deselect.....	18
Duplicate.....	18
Duplicate Linked.....	18
Copy.....	18
Paste.....	18
Delete.....	18
Delete Hierarchy.....	18
Unlink.....	18
ID Data.....	19
Unlink.....	19
Make Local.....	19
Make Single User.....	19
Delete.....	19
Remap Users.....	19
Copy.....	19
Paste.....	19
Add Fake User.....	19
Clear Fake User.....	19
Rename.....	19
Select Linked.....	19
Outliner ID Data Operation.....	20
Unlink.....	20
Make Local.....	20
Delete.....	20
Remap Users.....	20
Copy.....	20
Paste.....	20
Add Fake User.....	20
Clear Fake User.....	20
Rename.....	20
Select Linked.....	20
Mark as Asset.....	21
Clear Asset.....	21
Clear Asset (Set Fake User).....	21
Outliner Animation Data Property.....	21
Clear Animation Data.....	21
Set Action.....	21
Unlink Action.....	21

Refresh Drivers.....	21
Clear Drivers.....	21
Outliner Modifier Operation.....	21
Apply.....	21
Delete.....	21
Toggle Viewport Use.....	22
Toggle Render Use.....	22
Mark as Asset.....	22
Clear Asset.....	22
Clear Asset (Set Fake User).....	22
Level Restrictions.....	22
Selectability.....	22
Hide from Viewport.....	22
Hide from Render.....	22
Scenes Mode.....	23
Collection Menu.....	23
Move to Collection.....	23
Last Operator Move to Collection.....	23
Name.....	23
Link to Collection.....	23
Last Operator Link to Collection.....	24
Name.....	24
Remove From Collection.....	24
Remove From all Unlinked Collections.....	24
Add selected To Active Collection.....	24
Remove Selected From Active Collection.....	24
Add Collection.....	24
New Scene.....	24
New.....	24
Copy Settings.....	24
Linked Copy.....	24
Full Copy.....	25
Filter.....	25
Restriction Toggles.....	25
Sort Alphabetically.....	25
Sync Selection.....	25
Show Mode Column.....	25
Search.....	25
Exact Match Search.....	25
Case Sensitive Search.....	25
View Layer Mode.....	26
Collection Menu.....	26
Move to Collection.....	26
Link to Collection.....	26
Remove From Collection.....	26
Remove From all Unlinked Collections.....	27
Add selected To Active Collection.....	27
Remove Selected From Active Collection.....	27
Add Collection.....	27
Filter.....	27
Restriction Toggles.....	27
Exclude from View Layer.....	27
Selectable.....	27


Hide in Viewport.....	27
Disable in Viewport.....	28
Disable in Renders.....	28
Holdout.....	28
Indirect only.....	28
Sort Alphabetically.....	28
Sync Selection.....	28
Show Mode Column.....	28
Search.....	28
Exact Match Search.....	28
Case Sensitive Search.....	28
Filter.....	28
Object State Filter.....	28
Invert.....	29
Sequence Mode.....	29
Sync Outliner Selection.....	29
Blender File Mode.....	29
Filter.....	29
Filter ID Type.....	29
Outliner Library Operation.....	29
Delete.....	30
Relocate.....	30
Reload.....	30
Data API Mode.....	30
Header tools.....	30
Edit Menu.....	30
Keying Set Add Selected.....	30
Keying Set Remove Selected.....	30
Add Drivers to Selected.....	30
Delete Drivers for Selected.....	30
Set Keying set.....	30
Add keyframe.....	31
Remove keyframe.....	31
Library Override Mode.....	31
Library Override View Mode.....	31
Properties.....	31
Hierarchies.....	31
Filter options.....	31
Sort alphabetically.....	31
Search.....	31
Exact match.....	31
Case sensitive.....	31
Filter.....	32
Filter ID Type.....	32
Unused Data Mode.....	32
Clean Up.....	32
Clean Up menu.....	32
Unused Data.....	32
Recursive Unused Data.....	33
Unused Linked Data.....	33
Recursive Unused Linked Data.....	33
Unused Local Data.....	33
Recursive Unused Local Data.....	33

Filter.....	33
Filter ID Type.....	33
Status column.....	33
Hotkey only functionality.....	34
Insert Keyframe - I.....	34
Delete Keying Set Keyframe - Alt I.....	34
Hide - H.....	34
Unhide - Alt H.....	34

Outliner

The Outliner is an editor where you can organize the data in your scene. It is in the View Layer mode basically a list of the available objects and data in the scene, which is organized in so called collections. Think of it as a container that carries the scene data. This also includes things like brushes, textures and materials.

The outliner not only lists the data. But you can modify the data in various ways. And it has more than one mode. We will go through them, one by one.




The outliner has some context menus that are available by a right click at an element. We will also cover them, one by one.

General hotkey functionality

There is some general hotkey functionality that works across the whole interface. And so it works in the outliner too.

Left click at an object selects it. When you select an object in the outliner, then it is also selected in the scene.

Dragging the mouse with left click box selects.



Like in the 3D view, Shift + LMB adds to the selection, or can remove the clicked object from the selection.

Ctrl+LMB enters the rename mode for the object. You can also double click at it. In both cases the text becomes editable.



You can drag objects into the hierarchy of other objects, and make them a

child object by that.

You can navigate with the arrow buttons. Holding shift while navigating with the arrow buttons will extend the selection.


Delete hotkey deletes the selected items. Also selected collections.

Extended Functionality

The outliner has some extended functionality in some modes.

Objects with an arrow sign at the left are hierarchical objects. Hierarchy can be expanded and collapsed by clicking at the + and - signs.

When you click at a data block of some object types object, like the mesh component for a mesh or a curve object, then you will jump from object mode into edit mode. And vice versa.



Collections


Collections are containers that can contain objects or anything else in the scene. They can also include collections, and are fully recursive.

Header - All Modes

The header content changes, dependent of the display mode. Here we list the elements that are available in all display modes.


Switch to Properties Editor / Outliner

Sometimes you want to switch from Outliner to the Properties Editor, or vice versa. Since you sometimes don't have enough space for both, and end in dragging the borders of the editors around all the time. This two editors are connected by a menu that allows exactly that. A button in each header that switches to the other editor.




Display Mode

The Outliner has more than one purpose and workspace. In this drop down menu you can switch to different display modes. The available Modes are Scenes, View Layer, Sequence, Blender File, Data API and Unused Data. We will cover their functionality in their own chapters.




View Menu

The View menu contains general view related functionality.



Show Active

Centers the view of the list to the active object.




Show One Level

Expands the list hierarchy level by one.

Hide One Level

Collapses the list hierarchy level by one.



Expand / Collapse All


Expands or collapses all collapsed hierarchy. It's a toggle

Show Hierarchy

Open all object entries and close all others. For example, when you are in Scene view, and have the objects expanded, then the Show Hierarchy closes the objects hierarchy.

Box Select

Box select items in the list.



Select All

Select all items in the list.

Deselect All


Deselect all items in the list.

Invert Selection

Inverts the selection. Unselected list items becomes selected, selected list items becomes unselected.

Manage Unused Data

This opens a pop-out floating Outliner Editor in the Unused Data mode, so you can view and manage the unused data while remaining in the same Outliner mode.




Pie menus

Lists the available pie menus, and gives you the ability to read the hotkeys and assign own hotkeys.



Area

Area is a menu with window related settings.



Horizontal Split

Splits the editor horizontally into two editors.

Vertical Split

Splits the editor vertically into two editors.

Duplicate Area into new Window

Creates a floating window out of the current editor

Toggle Maximize Area

Displays the editor maximized with menus.

To return to split view press hotkey Ctrl Up Arrow, or reuse the menu item in the View menu.

Toggle Fullscreen Area

Displays the editor maximized without menus.

To return from the full screen view press hotkey Alt F10, or use the little button that appears up right when you move the mouse in this corner.

Close Area

Closes the area window.

Search Field

Search for specific terms in the list. When the search term matches a name in the list, then the list will center at the first entry with the match.



This search field is collapsible, and closed by default to free some UI space.

Right Click Menus


The Outliner comes with various right click functionality, dependent at what data you right click.

Outliner Scene Operation

This menu appears when you right click at a scene in Scene mode.

Delete

Deletes the currently selected scene.



Copy Settings

Creates an empty scene but also copies the settings from the active scene into the new one.

Linked Copy

This option creates a new scene with the same settings and contents as the active scene. However, instead of copying the objects, the new scene contains links to the objects in the old scene. Therefore, changes to objects in the new scene will result in the same changes to the original scene, because the objects used are literally the same. The reverse is also true.

Full Copy


Using this option, nothing is shared. This option creates a fully independent scene with copies of the active scene's contents. Every object in the original scene is duplicated, and a duplicate, private copy of its object-data is made as well.

Mark as Asset, Clear Asset, Clear Asset (Set Fake User)

Scenes cannot be stored in the asset library. This menu entries are redundant.


Outliner Data Operation

This menu appears at various object types and when you for example right click at the View Layer item. It also appears at objects in Data API mode, with varying content.



Select

Select the current element.



Deselect

Deselect the current element.

Hide

Hides the current element.

Unhide

Unhides the current element.

Select Linked

Does not show on all objects and tree elements. Selects the linked elements.

Mark as Asset, Clear Asset, Clear Asset (Set Fake User)

View Layers cannot be stored in the asset library. This menu entries are redundant.

Collection

This menu appears when you right click at a collection.

Clicking at a Scene collection will have not this much entries than clicking at the Collection item lower in the hierarchy.

New Nested

Create a new nested collection. There is no difference. Both gets added in the selected collection as a child, and the functionality is the same. Ask the Blender developers what they did here.

New

Create a new scene collection.

Duplicate Collection

Duplicates the currently selected collection, all its children, objects and the object data.

Duplicate Linked


Recursively duplicate the selected collection, all its children and objects, including linked object data.

Copy

Copies the collection.

Paste

Pastes a copied collection.



Delete

Delete the collection. Objects in the hierarchy will remain.

Delete Hierarchy

Delete the collection. Objects in the hierarchy will be deleted too.

Select Objects

Select the objects in the collection.

Deselect Objects

Deselect the objects in the collection.

Instance to Scene

Instance selected collections to the active scene.

Unlink

Unlink selected collections from the active scene.

Visibility

Visibility is a sub menu with some visibility functionality. The greyed out menu items will become available when the functionality becomes available. For example, Show becomes available when something is hidden.



Isolate

Hide all but this collection and its parents.

Show All Inside


Reveals the collection and all its content.

Hide

Hides the collection.

Set Color Tag


Give the collections a colored icon.



ID Data

Data related operations.

The content differs, dependant of the collection element that you right click at. And in which display mode you are. Linked collections have different content.



Unlink

Does basically the same than delete. It unlinks all data, and removes the object from the scene.

Make Local

For appended or linked data. Makes the selected object a local copy in the current blend file.

Add Library Override

Add a local library override to this collection.

This tool works different from Make Override in the outliner. It does not iterate through the hierarchy of objects and collections based on the selection. But works just for the currently selected object.

Library Overrides is the new system designed to replace and supersede Proxies. Most types of linked data-blocks can be overridden, and the properties of those overrides can then be edited. When the library data change, unmodified properties of the override one will be updated accordingly.

Make Single User

For duplicated content. Makes the data block of the selected object a single user.

Delete

Not functional in all situations. In the Unused Data mode you can remove objects with this.

Remap Users

Remaps the user of a data block to another one of the same type. This allows you to replace all usages of a material or texture by another one.

Copy

Copies the user data block.

Paste

Pastes a copied user data block.

Make Library Override Editable

Just with a linked collection. Make a single, out of hierarchy, local override of this linked data.

This only applies to the active outliner item.

Make Library Override Hierarchy

Just with a linked collection. Make a local override of this linked data and its hierarchy of dependencies. Means the collection becomes local to the current blend file. And the hierarchy gets revealed.

This only applies to the active outliner item.

Reset Library Override

Just with a local made linked collection, by Make Library Override Hierarchy.

Reset this local override to its linked values.

Reset Library Override Hierarchy

Reset this local override to its linked values, including its hierarchical dependencies.

Resync Library Override Hierarchy

Rebuild this local override from its linked reference, including its hierarchical dependencies.

Resync Library Override Hierarchy Enforce

Rebuild this local override from its linked reference, including its hierarchical dependencies. But enforce the hierarchy to match the linked data. This ignores existing overrides on data pointer properties.

Delete Library Override Hierarchy

Deletes the selected element.

Clear Single Library Override

Deletes this local override if possible. If not reset it and mark it as not editable.

Copy

Copies the selected element.

Paste

Pastes the selected element.

Add Fake User

Adds a fake user to the selected object. Fake users is an odd concept to keep data in the scene even if it has no user somewhere. The fake user is then a dummy user so that the object is not deleted when saving the scene.

Clear Fake User

Removes the fake user from the selected object.

Rename


Rename the object in the outliner.

Select Linked

Selects all objects that are linked to the currently selected one.

Make Library Override

Library Overrides is a system designed to allow editing linked data, while keeping it in sync with the original library data. Most types of linked data-blocks can be overridden, and the properties of these overrides can then be edited.



Selected

Add a library override to the selected collection.

Content


Add a library override to the content of the selected collection.

Selected & Content

Add a library override to both, the content of the selected collection, and the selected collection.

Reset Library Override

Library Overrides is a system designed to allow editing linked data, while keeping it in sync with the original library data. Most types of linked data-blocks can be overridden, and the properties of these overrides can then be edited.



Selected

Reset a library override to the selected collection.

Content


Reset a library override to the content of the selected collection.

Selected & Content

Reset a library override to both, the content of the selected collection, and the selected collection.

Clear Library Override

Library Overrides is a system designed to allow editing linked data, while keeping it in sync with the original library data. Most types of linked data-blocks can be overridden, and the properties of these overrides can then be edited.



Selected

Clear the library override to the selected collection.

Content

Clear the library override to the content of the selected collection.

Selected & Content

Clear the library override to both, the content of the selected collection, and the selected collection.

Troubleshoot Library Override

Troubleshoot library Override operators are useful to help synchronize or remove overrides without needing to reload scene or the linked file.



Resync

Rebuild the selected library overrides.

Resync Enforce

Rebuild the selected library overrides, enforcing libraries to match the linked data.

Delete

Delete the selected local library overrides. And relink the usage to the selected data.

Mark as Asset

Adds the collection to the asset library.

Clear Asset


Removes the collection from the asset library.

Clear Asset (Set Fake User)

Removes the collection from the asset library. But marks it with a fake user so that it remains in the scene.

Object Menu

This menu appears when you click at an object type. A mesh, a lamp, a camera ...



Select

Selects the object.

Select Hierarchy

Selects the object and its hierarchy.

Deselect

Deselects the object.

Duplicate

Duplicates the currently selected object and the object data.

Duplicate Linked

Duplicates the selected objec, including linked object data.

Copy

Copies object.

Paste

Pastes copied object.

Delete

Deletes the selected object. Child objects gets unparented.

Delete Hierarchy

Deletes the selected object and all its child objects.

Unlink

Deletes the selected object.

ID Data

Data related operations. Note that the tool tips are currently missing here.

Unlink

Does basically the same than delete. It unlinks all data, and removes the object from the scene.

Make Local

For appended or linked data. Makes the selected object a local copy in the current blend file.

Make Single User

For duplicated content. Makes the data block of the selected object a single user.

Delete

Not functional in all situations. In the Unused Data mode you can remove objects with this.

Remap Users

Remaps the user of a data block to another one of the same type. This allows you to replace all usages of a material or texture by another one.

Copy

Copies ID data.

Paste

Pastes copied ID data.

Add Fake User

Adds a fake user to the selected object. Fake users is an odd concept to keep data in the scene even if it has no user somewhere. The fake user is then a dummy user so that the object is not deleted when saving the scene.

Clear Fake User


Removes the fake user from the selected object.

Rename

Rename the object in the outliner.

Select Linked

Selects all objects that are linked to the currently selected one.



Outliner ID Data Operation

This menu appears when you for example click at the mesh component of a mesh object. It is the same content than the ID Data menu from the Object menu.

Unlink

Does basically the same than delete. It unlinks all data, and removes the object from the scene.

Make Local

For appended or linked data. Makes the selected object a local copy in the current blend file.

Delete

Not functional in all situations. In the Unused Data mode you can remove objects with this.

Remap Users

Remaps the user of a data block to another one of the same type. This allows you to replace all usages of a material or texture by another one.

Copy

Copies ID data.

Paste

Pastes copied ID data.

Add Fake User

Adds a fake user to the selected object. Fake users is an odd concept to keep data in the scene even if it has no user somewhere. The fake user is then a dummy user so that the object is not deleted when saving the scene.

Clear Fake User


Removes the fake user from the selected object.

Rename

Rename the object in the outliner.

Select Linked

Selects all objects that are linked to the currently selected one.



Mark as Asset

Adds the collection to the asset library.

Clear Asset


Removes the collection from the asset library.

Clear Asset (Set Fake User)

Removes the collection from the asset library. But marks it as fake user so that it remains in the scene.

Outliner Animation Data Property

This menu appears with a right click at an Animation data.




Clear Animation Data

Removes the whole animation.



Set Action

Opens a popup menu where you can choose the action for this object.



Unlink Action

Removes the action.

Refresh Drivers

Refreshes existing drivers.

Clear Drivers

Removes existing drivers.

Outliner Modifier Operation


This menu appears with a right click on modifiers.

Apply

Applies the modifier.

Delete

Removes the modifier.



Toggle Viewport Use

Toggles the visibility of the modifier in viewport.

Toggle Render Use

Toggles the visibility of the modifier on render time.

Mark as Asset

Adds the collection to the asset library.

Clear Asset

Removes the collection from the asset library.

Clear Asset (Set Fake User)

Removes the collection from the asset library. But marks it as fake user so that it remains in the scene.

Level Restrictions

Some list items have so called level restrictions. You can click at them, and so exclude the object from specific things. You can make more level restrictions available in the filter settings, which will be covered below. The by default activated are:



Selectability

Makes the object unselectable in the viewport. Or disables it, in case of a collection for example.

Hide from Viewport

Hides the object from the Viewport.


Hide from Render

Excludes the object from rendering.


Scenes Mode

The Scenes mode starts one hierarchy higher than the default View Layer Mode. It shows all available scenes and their content.

Normally you work with one scene. And so the default starts with the View Layer mode of the scene. But you can create more scenes in the Properties Editor in the Scene tab.





Collection Menu



Move to Collection

Moves the selected object to a collection. The object is removed from the collection it was in.



Last Operator Move to Collection

Name



Set a name for your new collection. When you haven't created a new collection, then this name stays blank.



Link to Collection

Links the object to a collection. The object remains in the collection it was in.

By clicking at this menu item a popup will appear to choose the collection. Here you can also create a new collection. Once done, the object will be linked to this new created collection.



Last Operator Link to Collection

Name

Set a name for your new collection. When you haven't created a new collection, then this name stays blank.



Remove From Collection

Objects can be in more than one collection. Remove from collection removes the selected object from the current collection.

When the object is in no collection anymore, then it gets removed.

Remove From all Unlinked Collections

Objects can be in more than one collection. Remove from all unlinked collection removes the selected object from all unlinked collections.

When the object is in no collection anymore, then it gets removed.

Add selected To Active Collection

Objects can be in more than one collection. Adds the selected object to the active collection.

Remove Selected From Active Collection

Objects can be in more than one collection. Removes the selected object from the active collection.

When the object is in no collection anymore, then it gets removed.

Add Collection




Add a collection inside of the current selected collection.

New Scene

New

Creates an empty scene with default values.



Copy Settings

Creates an empty scene but also copies the settings from the active scene into the new one.

Linked Copy

This option creates a new scene with the same settings and contents as the active scene. However, instead of

copying the objects, the new scene contains links to the objects in the old scene. Therefore, changes to objects in the new scene will result in the same changes to the original scene, because the objects used are literally the same. The reverse is also true.

Full Copy


Using this option, nothing is shared. This option creates a fully independent scene with copies of the active scenes contents. Every object in the original scene is duplicated, and a duplicate, private copy of its object-data is made as well.

Filter

Options and filter settings.

Restriction Toggles

Enable or disable further level restrictions. Note that these toggles shows when you expand a scene hierarchy. Scenes itself have no such toggles.



Sort Alphabetically

Sorts the content of the outliner in alphabetically order.

Sync Selection

Synchronize the selection between outliner and 3d view.

Show Mode Column

Display the Mode column at the left. When you are not in object mode, but in edit mode, or in vertex paint mode etc., then a mode icon is displayed at the left of the object that you currently edit.



Search

Exact Match Search


The search result must fit exactly. For example, when you search for cam, then a camera should not display as a search result.

Case Sensitive Search


Search case sensitive.

View Layer Mode

The view layer mode shows the content of the current View Layer. This is the default mode.





Collection Menu



Move to Collection

Moves the selected object to a collection. The object is removed from the collection it was in.



By clicking at this menu item a popup will appear to choose the new collection. Allows also to create a new collection. Once done, the object will be moved to this new created collection.



Link to Collection

Links the object to a collection. The object remains in the collection it was in.

By clicking at this menu item a popup will appear to choose the collection. Here you can also create a new collection. Once done, the object will be linked to this new created collection.



Note that there is a tool called Add to collection in the Object Properties in the Collections panel that does a similar job. It links an object to other collections. But this Link to Collection tool here just lists the collections in the current view layer.

Remove From Collection

Objects can be in more than one collection. Remove from collection removes the selected object from the current collection.

When the object is in no collection anymore, then it gets removed.

Remove From all Unlinked Collections

Objects can be in more than one collection. Remove from all unlinked collection removes the selected object from all unlinked collections.

When the object is in no collection anymore, then it gets removed.

Add selected To Active Collection

Objects can be in more than one collection. Adds the selected object to the active collection.

Remove Selected From Active Collection

Objects can be in more than one collection. Removes the selected object from the active collection.

When the object is in no collection anymore, then it gets removed.

Add Collection




Add a collection inside of the current selected collection.

Filter

Options and filter settings.

Restriction Toggles

Enable or disable further level restrictions. To make the changes permanent you would have to save the startup file. This settings is part of the layout.



Exclude from View Layer

include / Exclude the collection from the view layer.

Selectable

Make the object selectable / unselectable.

Hide in Viewport

Show or hide the object in the viewport.

Disable in Viewport

Enable or disable the object in the viewport.

Disable in Renders

Enable or disable the object in the rendered result.

Holdout

Mask out objects in the collection from view layer.

Indirect only

Make the objects in the collection just distribute indirect lighting to the layer.

Sort Alphabetically

Sorts the content of the outliner in alphabetically order.

Sync Selection

Synchronize the selection between outliner and 3d view.

Show Mode Column

Display the Mode column at the left. When you are not in object mode, but in edit mode, or in vertex paint mode etc., then a mode icon is displayed at the left of the object that you currently edit.



Search

Exact Match Search


The search result must fit exactly. For example, when you search for cam, then a camera should not display as a search result.

Case Sensitive Search

Search case sensitive.


Filter

Shows or hides the object and data types. The names should be self explaining. Note that the Library Override option just shows for appended objects.




Object State Filter

Shows or hides objects by its state.




Invert

Inverts the object state filter.



Sequence Mode

This mode lists the loaded files when you work with the sequencer layout and have video material loaded.




Sync Outliner Selection

Keep the selection in synchronization with the other editors. 3D View and VSE.

Blender File Mode

This mode lists the whole content of the current Blender file. It includes also things like the default brushes, which comes from the startup defaults.




Filter

Enable a filter to display a specific data type. You can just filter by one data type at a time. The rest will be hidden.


Filter ID Type

The menu to choose the data type that should be displayed.



Outliner Library Operation

In this mode, you can see linked data from external ***.blend** files.




Grey arrows means the data is directly referenced from a linked ***.blend** file.

Green arrows means the data is indirectly referenced into another linked ***.blend** file.

Delete

Deletes linked libraries.



Relocate

Relocated the path of a linked library.

Reload


Reloads and refreshes the linked library in the current file.

Data API Mode

Displays Low Level Blender data and its properties.

This view also reveals some properties. Like File is Saved or Use Autopack.

When no keying set is defined then you will get a No Keying Set Active message instead of the Keying set element.




Blender Data		No Keying Set Active
Blendfile Data		
Filename		
File Has Unsaved Changes		
File is Saved		
Use Autopack		
Version	1 item	
Cameras	1 item	
Scenes	2 items	
Objects	0 items	
Materials	0 items	
Node Groups	0 items	
Meshes	0 items	
Lights	1 item	
Libraries	1 item	
Screens	7 items	
Window Managers	1 item	
Images	0 items	

Header tools

Edit Menu

Keying Set Add Selected

Add a keying set to the selected object.



Keying Set Remove Selected

Remove the keying set from the selected object.

Add Drivers to Selected

Add a driver to the selected object.

Delete Drivers for Selected

Delete a driver from the selected object.

Set Keying set

Choose a keying set.

Add keyframe

Adds a keyframe for the selected element.


Remove keyframe

Removes the current keyframe from the selected element.

Library Override Mode


Lists the library overrides in the scene.

This feature is experimental and this lousy documented in the Blender manual that it is not to find out what library overrides are and how to use them. None of the mentioned ways to create a library override works.




What you can read there though is how great they are, and that they replace the proxies. So here comes the outliner section for the great library overrides. Whatever it is ...

Library Override View Mode




Properties

Show the properties of the library overrides.



Hierarchies


Show the objects with library overrides in a hierarchical way.



Filter options

Sort alphabetically

Sorts the library overrides in alphabetical order in the outliner list.



Search

Search options.

Exact match

Search with exact match.

Case sensitive


Take upper and lower case status into account.

Filter

Enable a filter to display a specific data type. You can just filter by one data type at a time. The rest will be hidden.


Filter ID Type

The menu to choose the data type that should be displayed.



Unused Data Mode

Bforartists has a special system to treat not longer used data. Unused data will normally remain in the scene as long as you haven't saved it and reloaded it. Means delete does not immediately remove a mesh completely from the scene for example. It will be unused data now. Until you save and reopen the scene. The cleanup process happens at saving the blend file.



The Unused Data allows you to clean up the unused data without to save and reload the blend file. It lists all data that has no user in the scene. This includes the standard brushes from the startup configuration. Don't delete them!

Clean Up


Normally you would need to save the blend file and reload it to get rid of the unused data. Clean Up removes all unued data from the blend file immediately. Note that this does not remove objects with a fake user associated.

Clean Up menu

The clean up button cleans up what is in the list. This is good enough for most cases. But sometimes you might want to have a bit more fine control.

Unused Data

Removes unused data blocks.



Recursive Unused Data

Recursively removes unused data blocks. Means the child objects gets removed too.

Unused Linked Data

Removes unused data that is linked to this file.

Recursive Unused Linked Data

Recursively removes unused data that is linked to this file. Means the child objects gets removed too.

Unused Local Data

Removes unused local data.

Recursive Unused Local Data


Recursively removes unused local data. Means the child objects gets removed too.

Filter

Enable a filter to display a specific data type. You can just filter by one data type at a time. The rest will be hidden.

Filter ID Type

The menu to choose the data type that should be displayed.



Status column

The number at the right tells you how many users the object has.

Objects with a power icon and an F besides the number have a fake user assigned. Objects with an X in the row is unused data, and will be removed with the next save and reload of the blend file. Objects with the power icon will remain in the scene. They have a fake user.

To remove the Fake User at an object click at the Power icon. It will turn into the X button then. And the object will be removed at saving.



Hotkey only functionality

Important! These hotkeys works with the default Bforartists key map And they do not list the Ndof hotkeys. Ndof is a 3d connexion mouse device that is also used for tablets.

Most of the tools can be found in the graphical UI. But there are still some tools that are hotkey only. Some have a UI brother with equal functionality. For example, Pick shortest path is the hotkey sister of Select shortest path. Some are hotkey only since they cannot be integrated in the graphical UI. Like calling the File menu under the mouse. Or mouse position dependent functionality like selecting an edge loop.

The navigation hotkeys and the context menus are excluded here since they are already covered.

Insert Keyframe - I

Insert a keyframe at current position. You need to have a keying set added to the object.

Delete Keying Set Keyframe - Alt I

Remove existing keyframes.

Hide - H

Hides the object in the 3d view.

Unhide - Alt H

Unhides all hidden objects in the 3d view.